

TECHNOLOGY



AccurioWide 200

2 METER HYBRID UV LED WIDE FORMAT INKJET PRINTER

High-quality image resolution up to 720 x 1,440 dpi

Vivid color prints

Low ink consumption

Advanced layered white ink printing

Droplet size of 12 pl color ink and 30 pl white ink

Color configuration of 6 color + white

High productivity of five printing modes

Immediate curing with UV LED lamps

Long lasting LED lamps for at least 10,000 hours

Strong vacuum, belt-driven for flawless media handling

Wide range of media types

Rigid and flexible roll media types

Media thickness from 0.04" up to 1.77"

Borderless printing up to 6.6'

Konica Minolta 1024i printhead technology

Fade-resistant, long-lasting, curable UV ink for indoor and outdoor applications

Thin ink layering

Text quality of 4 points

AccurioPro WideDirector workflow

Powerful RIP software and dedicated server

AccurioWide 200

2 METER HYBRID UV LED WIDE FORMAT INKJET PRINTER

AccurioWide 200 gives you the versatility of printing on rigid or flexible materials with just one printer. You can print on almost any substrate with ease, up to a thickness of 1.77". Job applications are endless to meet your customers' demand. Using a thin ink layering technology while maintaining high densities, you will see substantial savings on consumables while maintaining perfectly vivid and bright colors.

MFDIA Δ	ND PRINTING SI	PECIFICATIONS	- RIGID MEDIA

Max. width	6.7' (205 cm)
	6.6' (200 cm) with borderless printing
Max. length	10.5' (3.2 m) — 4 rigid tables (2 front and 2 rear)
Min. size	A2 landscape — 1.97' x 1.4' (60 x 42 cm)
Thickness	Min.: 0.04" (1 mm)
	Max.: 1.77" (45 mm)
Max. weight	2 lbs/ft ² (10 kg/m ²) on printing table

MEDIA AND PRINTING SPECIFICATIONS — FLEXIBLE MEDIA

MEDIA AND I KINTING SI ECII IOATIONS TELADEL MEDIA	
Max. width	6.7' (205 cm)
	6.6' (200 cm) with borderless printing
Max. length	N/A — restricted by weight and diameter
Min. thickness	0.2 mm
Max. weight	110 lb (50 kg)
Max. roll outside diameter	Support for 3" core-media rolls with
	max. outside diameter 14.17" (36 cm)

PRINT SPEED

Draft mode	Up to 1,119 ft ² /hr (104m ² /hr)	
Express mode	689-764 ft ² /hr (64-71 m ² /hr)	
Production mode	344-560 ft ² /hr (32-52 m ² /hr)	
Standard mode	204-301 ft ² /hr (19-28 m ² /hr)	
High-quality mode	86-161 ft ² /hr (8-15 m ² /hr)	

PRINTHEADS

PRINTIFICADO	
2 KM 1024i printheads (white)	6 color + white — 1,024 nozzles/head
	with droplet volume of 30 pl (white in-line)
6 KM 1024i printheads (color) 6 color + white — 1,024 nozzles/head	
	with droplet volume of 12 pl (colors)

INK CHANNELS

UV ink*	6 color + 2 white - CMYKLcLm + white
---------	--------------------------------------

*ACCURIOWIDE INK has achieved GREENGUARD GOLD certification. GREENGUARD Certified products are certified to UL standards for low chemical emissions into indoor air during product usage. For more information, visit: ul.com/gg.



Ink reservoir capacity	Color: 4 L White: 2.7 L
IMAGE AND TEXT QUALITY	
High-quality prints	Up to 720 x 1,440 dpi
Text quality	Positive: 4 points
	Negative: 6 points

ENGINE DIMENSIONS AND WEIGHT

Main unit dimensions

(H x W x D)

Main unit weight	3,968 lb (1,800 kg)
Without swivel arm.	
MEDIA TABLES	
Small media tables	41.7" x 88" x 25"
(H x W x D)	(106.7 x 223.5 x 63.5 cm)
Weight	88 lb (40 kg)

70" x 177" x 63" (177 x 450* x 160 cm)

POWER REQUIREMENTS AND COMPRESSED AIR

Power requirements	208/240 V AC, 3-phase no neutral with ground wire, 60 Hz, Max
(customer provided)	24A. Plug & Receptacle must be provided by Certified Electrician.
Air compressor	Oil-free (Class-1 according to ISO 8573-1 2010)
(customer provided)	160 L/min compressor with 50 L barrel at 87 psi

SYSTEM INTEGRATION RIP / WORKFLOW SOFTWARE

AccurioPro WideDirector	Single processor — (1) Intel Core i9 10850k 3.60/5.20 GHz
server	Turbo Boost 10 cores/20 threads
AccurioPro WideDirector	Production suite, 3rd party RIP integration is possible
software	
AccurioPro WideDirector	Dongle (license)
starter	

WORKFLOW FEATURES

TOTAL LOTT I EM ONLO	
Seamless print support	Optional
XML to JDF connector	Optional
One-way vision creation	Optional
Production dashboard	Optional

PRINTER ACCESSORIES

I Idill'I Ell'AlooEsso Idies	
Dedicated roll-to-roll	Included
	Weight: 110 lb (50 kg)
Large media tables	Included
(H x W x D)	2 tables per set
	Folded: 42.1" x 85.8" x 39" (107 x 218 x 99 cm)
	Unfolded: 42.1" x 85.8" x 72.8" (107 x 218 x 185 cm)
	Weight: 132 lb (60 kg) each table

CONSUMABLES

CONSONIADEES	
AccurioWide ink	2 x 1 L cyan
	2 x 1 L magenta
	2 x 1 L yellow
	2 x 1 L black
	2 x 1 L light cyan
	2 x 1 L light magenta
	2 x 0.9 L white
	2 x 1 L flush
Printhead wipes	Berkshire wipes (50 wipes per bag)
Start-up media	Polyester adhesive backed vinyl (152.5 cm x 15 m)

AccurioPro WideDirector

Server	Intel Core i9 10850K
	3.6 GHz/5.2GHz Turbo Burst Speed
	10 cores/20 Threads HyperThreading
	32 GB DDR4 2666 GHz memory
	2TB Disk Drive, 480 GB Intel Drive for OS

For detailed speci ications, see data sheets.

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission $is prohibited. KONICA\ MINOLTA\ and\ the\ KONICA\ MINOLTA\ logo\ are\ registered\ trademarks\ or\ trademarks\ of\ KONICA\ MINOLTA\ , INC.\ All\ other\ product$ and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com





